




### Brand-Rex Copper Connectivity - GigaPlus Modules

Category 5e Slimline Shuttered Modules - Shielded and Unshielded



#### Product Part Numbering

	Unshielded	Shielded
50mm x 25mm Slimline Shuttered Module - White	GPCSL062UB03	GPCSL062SB03
50mm x 25mm Slimline Shuttered Module - Black	GPCSL062UB02	GPCSL062SB02
38mm x 25mm Slimline Shuttered Module - White	GPCSL06CUB03	GPCSL06CSB03
38mm x 25mm Slimline Shuttered Module - Black	GPCSL06CUB02	GPCSL06CSB02
50mm x 25mm Angled Slimline Shuttered Module - White	GPCSLA62UB03	GPCSLA62SB03
50mm x 25mm Angled Slimline Shuttered Module - Black	GPCSLA62UB02	GPCSLA62SB02

#### PRODUCT DESCRIPTION:

GigaPlus Slimline Shuttered Modules offer true Category 5e component performance and are fully compatible with Brand-Rex UK and continental UNI style faceplates and products, and are suitable for applications where internal back box space is limited. Each jack is supplied with a shortform installation instruction and a cable tie to attach the cable to the cable anchor. Modules are supplied with a colour code wiring label.

#### PRODUCT CHARACTERISTICS:

Outlet Style:	Shielded / Unshielded Keystone type with unkeyed RJ-45 ports
Cable Entry:	Rear and Top
Colour:	Black or White
Body Material:	High impact ABS UL94 - VO
Jack Contacts:	Phosphor Bronze
Plating:	50 µm Gold over 100 µm of nickel
Punch Down Blocks:	Universal IDC
IDC Contacts:	Phosphor Bronze
Wiring Standard:	EIA/TIA 568B
Conformance:	ISO/IEC 11801 : 2002 & Amm1, ANSI/EIA/TIA 568C EN50173-1 : 2007